

MULE PRO-MX



SPECS

POWER

Maximum Power	33 kW {45 PS} / 6,000 rpm
Maximum Torque	58 Nm {5.9 kgfm} / 5,000 rpm
Engine	4-stroke Single
Displacement	695 cc
Bore x Stroke	102.0 x 85.0 mm
Compression Ratio	10.3:1
Valve System	SOHC, 4 valves per cylinder
Fuel System	Fuel injection: \varnothing 44 mm x 1
Ignition	Battery & coil
Starting	Electric
Cooling	Liquid-cooled
Lubrication	Forced lubrication, wet sump
Transmission	Dual-range (high/low) CVT with centrifugal clutch and reverse
Primary Reduction Ratio	0.791 ~ 2.451
Gear Ratio: Forward (High)	3.486 (27/25 x 46/19 x 24/18)
Gear Ratio: Forward (Low)	6.646 (35/17 x 46/19 x 24/18)
Gear Ratio: Reverse	5.311 (39/26 x 34/31 x 46/19 x 24/18)
Final Reduction Ratio: Front	4.375 (35/8)
Final Reduction Ratio: Rear	4.375 (35/8)
Final Drive	2WD/4WD, shaft, dual-mode differential

CAPABILITY

Frame	Ladder type, tubular steel
Front Suspension	Double wishbone
Rear Suspension	Double wishbone
Front Wheel Travel	218 mm
Rear Wheel Travel	232 mm
Steering	Rack and pinion with Electric Power Steering
Rake	5.0°
Trail	-
Steering Angle (L/R)	40° (IN) / 30° (OUT), 40° (IN) / 30° (OUT)
Front Tyres	25 x 8.00R12
Rear Tyres	25 x 10.00R12
Front Brakes	Dual \varnothing 212 mm discs
Front Calipers	Two-piston

Rear Brake/s	Dual ø212 mm discs
Rear Caliper/s	Single-piston
Parking Brake	Dual discs (mechanical)

DETAILS

Dimensions (LxWxH)	2,795 x 1,525 x 1,925 mm
Wheelbase	2,005 mm
Road Clearance	270 mm
Seat Height	850 mm
Curb Weight*	728 kg
Fuel Capacity	36 litres
Tread Front / Rear	1,322 mm / 1,285 mm
Turning Radius	4.2 m
Cargo Bed Dimensions (LxWxH)	847 x 1,119 x 232 mm
Cargo Bed Capacity	317 kg
Seating Capacity	2
Vehicle Load Capacity	544 kg
Towing Capacity	680 kg
Lighting	2x halogen, 2x LED headlights
Model Code	KAF700ERFNN