Kawasaki
Let the Good Times Roll

STOCKMAN



SPECS

POWER

Maximum Power	14.0 kW {19 PS} / 7,600 rpm
Maximum Torque	19.8 Nm {2.0 kgfm} / 6,100 rpm
Engine	4-stroke Single
Displacement	233 cc
Bore x Stroke	67.0 x 66.0 mm
Compression Ratio	9.4:1
Valve System	SOHC, 2 valves
Fuel System	Fuel injection: ø32 mm x 1
Ignition	Digital
Starting	Electric
Cooling	Air-cooled
Lubrication	Forced lubrication, wet sump
Transmission	6-speed, return
Primary Reduction Ratio	2.871 (89/31)
Gear Ratio: 1st	3.000 (39/13)
Gear Ratio: 2nd	2.067 (31/15)
Gear Ratio: 3rd	1.556 (28/18)
Gear Ratio: 4th	1.261 (29/23)
Gear Ratio: 5th	1.040 (26/25)
Gear Ratio: 6th	0.852 (23/27)
Final Reduction Ratio	3.214 (45/14)
Clutch	Wet multi-disc, manual
Final Drive	Chain

PERFORMANCE

Frame	Perimeter, high-tensile steel
Front Suspension	ø37 mm telescopic fork
Rear Suspension	New Uni Trak with adjustable spring preload
Front Wheel Travel	158 mm
Rear Wheel Travel	168 mm
Rake	25.4°
Trail	123 mm
Steering Angle (L/R)	45° / 45°
Front Tyre	80/100-21 51M
Rear Tyre	100/100-18 59M

Front Brake/s	ø265 mm petal disc
Front Caliper/s	Twin-piston
Rear Brake	ø220 mm petal disc
Rear Caliper	Single-piston

DETAILS

Dimensions (LxWxH)	2,105 x 920 x 1,110 mm
Wheelbase	1,350 mm
Road Clearance	220 mm
Seat Height	845 mm
Curb Weight*	137 kg
Fuel Capacity	7.5 litres
Model Code	KV230ARFNN