

KX250



SPECS

POWER

Engine	4-stroke Single
Displacement	249 cc
Bore x Stroke	78.0 x 52.2 mm
Compression Ratio	14.0:1
Valve System	DOHC, 4 valves
Fuel System	Fuel injection: \varnothing 44 mm x 1, with dual injectors
Ignition	Digital DC-CDI
Starting	Electric
Cooling	Liquid-cooled
Lubrication	Forced lubrication, semi-dry sump
Transmission	5-speed, return
Primary Reduction Ratio	3.350 (67/20)
Gear Ratio: 1st	2.077 (27/13)
Gear Ratio: 2nd	1.688 (27/16)
Gear Ratio: 3rd	1.438 (23/16)
Gear Ratio: 4th	1.235 (21/17)
Gear Ratio: 5th	1.045 (23/22)
Final Reduction Ratio	3.846 (50/13)
Clutch	Wet multi-disc, manual
Final Drive	Chain

PERFORMANCE

Frame	Perimeter, aluminium
Front Suspension	\varnothing 49 mm inverted fork with adjustable compression and rebound damping
Rear Suspension	New Uni Trak with adjustable dual-range (high/low-speed) compression damping, adjustable rebound damping and adjustable spring preload
Front Wheel Travel	305 mm
Rear Wheel Travel	307 mm
Rake	27.0°
Trail	118 mm
Steering Angle (L/R)	42° / 42°
Front Tyre	80/100-21 51M
Rear Tyre	110/90-19 62M
Front Brake/s	Semi-floating \varnothing 270 mm petal disc
Front Caliper/s	Dual-piston \varnothing 240 mm petal disc

Rear Brake
Rear Caliper Single-piston

DETAILS

Dimensions (LxWxH) 2,190 x 820 x 1,265 mm
Wheelbase 1,485 mm
Road Clearance 340 mm
Seat Height 955 mm
Curb Weight* 109.5 kg
Weight without Fuel 105.0 kg
Fuel Capacity 6.2 litres
Model Code KX252ESFNN

TECHNOLOGY



Dual Injectors



ERGO-FIT



KLCM (Kawasaki Launch Control Mode)



KTRC (Kawasaki Traction Control)



Power Modes



Smartphone Connectivity