Kawasaki
Let the Good Times Roll

MULE SX 4X4 XC



SPECS

POWER

Maximum Power	9.9 kW {13.5 PS} / 4,000 rpm
Maximum Torque	29.7 Nm {3.0 kgƒm} / 2,400 rpm
Engine	4-stroke Single
Displacement	401 cc
Bore x Stroke	82.0 x 76.0 mm
Compression Ratio	8.6:1
Valve System	OVH
Fuel System	Carburettor
Ignition	Magneto & transistor
Starting	Electric
Cooling	Air-cooled
Lubrication	Forced lubrication, wet sump
Transmission	2-speed automatic, forward/reverse
Primary Reduction Ratio	3.653 ~ 0.794 (belt converter)
Gear Ratio: Forward (High)	3.464 (35/24 x 38/16)
Gear Ratio: Forward (Low)	5.125 (41/19 x 38/16)
Gear Ratio: Reverse	4.453 (30/16 x 38/16)
Final Reduction Ratio: Front	3.852 (16/18 x 39/9)
Final Reduction Ratio: Rear	4.000 (64/16)
Final Drive	Gear, selectable 2WD/4WD, dual-mode differential

CAPABILITY

Frame	Ladder type, tubular steel
Front Suspension	Independent, MacPherson strut
Rear Suspension	Unit swing axle
Front Wheel Travel	78 mm
Rear Wheel Travel	79 mm
Steering	Rack and pinion
Rake	9°
Trail	50 mm
Steering Angle (L/R)	41° (IN) / 35° (OUT), 41° (IN) / 35° (OUT)
Front Tyres	26 x 9.00-12
Rear Tyres	26 x 9.00-12
Front Brakes	Dual hydraulic drums
Rear Brake/s	Dual hydraulic drums

Parking Brake	Mechanical, on rear wheels

DETAILS

Dimensions (LxWxH)	2,710 x 1,335 x 1,895 mm
Wheelbase	1,780 mm
Road Clearance	180 mm
Seat Height	830 mm
Curb Weight*	501 kg
Fuel Capacity	16 litres
Tread Front / Rear	1,080 mm / 1,050 mm
Turning Radius	3.6 m
Cargo Bed Dimensions (LxWxH)	905 x 1,040 x 245 mm
Cargo Bed Capacity	181 kg
Seating Capacity	2
Vehicle Load Capacity	398 kg
Towing Capacity	500 kg
Lighting	2x halogen headlights
Model Code	KAF400XSANN