Kawasaki
Let the Good Times Roll

# TERYX4 S LE



## SPECS

### POWER

| | |
|---|---|
| Maximum Power | 43 kW {58 PS} / 6,750 rpm |
| Maximum Torque | 64 Nm {6.5 kgfm} / 5,500 rpm |
| Engine | 4-stroke 90° V-Twin |
| Displacement | 783 cc |
| Bore x Stroke | 85.0 x 69.0 mm |
| Compression Ratio | 10.7:1 |
| Valve System | SOHC, 4 valves per cylinder |
| Fuel System | Fuel injection: ø36 mm x 2 |
| Ignition | Battery & coil (transistorised ignition) |
| Starting | Electric |
| Cooling | Liquid-cooled |
| Lubrication | Forced lubrication, wet sump |
| Transmission | Dual range CVT with centrifugal clutch and reverse |
| Primary Reduction Ratio | 2.788 ~ 0.725 (belt converter) |
| Gear Ratio: Forward (High) | 3.279 (28/26 x 30/19 x 27/14) |
| Gear Ratio: Forward (Low) | 5.553 (31/17 x 30/19 x 27/14) |
| Gear Ratio: Reverse | 4.568 (16/12 x 18/16 x 30/19 x 27/14) |
| Final Reduction Ratio: Front | 4.375 (35/8) |
| Final Reduction Ratio: Rear | 4.400 (44/10) |
| Final Drive | 2WD/4WD, shaft |

### CAPABILITY

| | |
|---|---|
| Frame | Double-X reinforcement type, tubular carbon steel |
| Front Suspension | Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping |
| Rear Suspension | Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping |
| Front Wheel Travel | 272 mm |
| Rear Wheel Travel | 254 mm |
| Steering | Rack and pinion with Electric Power Steering |
| Rake | 7° |
| Trail | 39 mm |
| Steering Angle (L/R) | 37° (IN) / 32° (OUT), 37° (IN) / 32° (OUT) |
| Front Tyres | MAXXIS Bighorn 2.0 27 x 9R14 6PR |
| Rear Tyres | MAXXIS Bighorn 2.0 27 x 11R14 6PR |
| Front Brakes | Dual ø200 mm discs |

| | |
|---|---|
| Front Calipers | Two-piston |
| Rear Brake/s | Enclosed wet multi-plate |
| Parking Brake | Enclosed wet multi-plate |

## DETAILS

| | |
|---|---|
| Dimensions (LxWxH) | 3,185 x 1,590 x 2,045 mm |
| Wheelbase | 2,240 mm |
| Road Clearance | 285/310 mm (standard/max preload) |
| Seat Height | 865 (F) / 930 (R) mm |
| Curb Weight* | 743 kg |
| Fuel Capacity | 30 litres |
| Tread Front / Rear | 1,400 mm / 1,330 mm |
| Turning Radius | 5.4 m |
| Cargo Bed Dimensions (LxWxH) | 455 x 1,210 x 220 (F) / 125 (R) mm |
| Cargo Bed Capacity | 113 kg |
| Seating Capacity | 4 |
| Vehicle Load Capacity | 499 kg |
| Towing Capacity | 590 kg |
| Lighting | 4x LED headlights |
| Model Code | KRT800JSFAN |

## TECHNOLOGY



ERGO-FIT