

# NINJA ZX-6R



## SPECS

### POWER

|                            |                                                    |
|----------------------------|----------------------------------------------------|
| Maximum Power              | 91.0 kW {124 PS} / 13,000 rpm                      |
| Maximum Power with Ram Air | 95.2 kW {129 PS} / 13,000 rpm                      |
| Maximum Torque             | 69.0 Nm {7.0 kgfm} / 11,000 rpm                    |
| Engine                     | 4-stroke In-Line Four                              |
| Displacement               | 636 cc                                             |
| Bore x Stroke              | 67.0 x 45.1 mm                                     |
| Compression Ratio          | 12.9:1                                             |
| Valve System               | DOHC, 16 valves                                    |
| Fuel System                | Fuel injection: ø38 mm x 4 with oval sub-throttles |
| Ignition                   | Digital                                            |
| Starting                   | Electric                                           |
| Cooling                    | Liquid-cooled                                      |
| Lubrication                | Forced lubrication, wet sump                       |
| Transmission               | 6-speed, return                                    |
| Primary Reduction Ratio    | 1.900 (76/40)                                      |
| Gear Ratio: 1st            | 2.846 (37/13)                                      |
| Gear Ratio: 2nd            | 2.200 (33/15)                                      |
| Gear Ratio: 3rd            | 1.850 (37/20)                                      |
| Gear Ratio: 4th            | 1.600 (32/20)                                      |
| Gear Ratio: 5th            | 1.421 (27/19)                                      |
| Gear Ratio: 6th            | 1.300 (26/20)                                      |
| Final Reduction Ratio      | 2.867 (43/15)                                      |
| Clutch                     | Wet multi-disc, manual                             |
| Final Drive                | Chain                                              |

### PERFORMANCE

|                      |                                                                                                                                    |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Frame                | Perimeter, pressed-aluminium                                                                                                       |
| Front Suspension     | ø41 mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability                                |
| Rear Suspension      | Bottom-Link Uni Trak, gas-charged shock with piggyback reservoir, compression and rebound damping and spring preload adjustability |
| Front Wheel Travel   | 120 mm                                                                                                                             |
| Rear Wheel Travel    | 151 mm                                                                                                                             |
| Rake                 | 23.5°                                                                                                                              |
| Trail                | 101 mm                                                                                                                             |
| Steering Angle (L/R) | 27° / 27°                                                                                                                          |

|                 |                                          |
|-----------------|------------------------------------------|
| Front Tyre      | 120/70ZR17M/C (58W)                      |
| Rear Tyre       | 180/55ZR17M/C (73W)                      |
| Front Brake/s   | Dual semi-floating ø310 mm discs         |
| Front Caliper/s | Radial-mount, monobloc, opposed 4-piston |
| Rear Brake      | ø220 mm disc                             |
| Rear Caliper    | Single-bore pin-slide aluminium-piston   |

## DETAILS

|                        |                        |
|------------------------|------------------------|
| Dimensions (LxWxH)     | 2,025 x 710 x 1,105 mm |
| Wheelbase              | 1,400 mm               |
| Road Clearance         | 130 mm                 |
| Seat Height            | 830 mm                 |
| Curb Weight*           | 198 kg                 |
| Estimated Dry Weight** | 179 kg                 |
| Fuel Capacity          | 17 litres              |
| Model Code             | ZX636JTFAN             |

## TECHNOLOGY

- 

ABS (Anti-lock Brake System)
- 

Dual Throttle Valves
- 

Economical Riding Indicator
- 

Assist & Slipper Clutch
- 

KIBS (Kawasaki Intelligent anti-lock Brake System)
- 

KQS (Kawasaki Quick Shifter)
- 

KTRC (Kawasaki Traction Control)
- 

Power Modes
- 

Smartphone Connectivity